

FLOTT Metal band saw PBS 120 Plus



3D object – Separation from
the base plate – Detail
(optional)



3D object – Separation from
the base plate
(optional)

Standard equipment

- ▶ Portable manual metal band saw with two band speeds for mitre cuts from 0° to 60°
- ▶ Manual arm feed to the cut
- ▶ Two band speeds
- ▶ Saw blade guide made from carbide
- ▶ Cast iron vice with quick-release lever
- ▶ Option to connect a longitudinal stop
- ▶ Saw blade cooling at the point of machining
- ▶ incl. saw blade combi-toothing 8/12
- ▶ 12-month warranty for single-shift operation

Accessories

- ▶ Underframe
can only be ordered together with coolant tray
Order no. 570.508
- ▶ Coolant tray
(can only be ordered together with underframe)
Order no. 570.509
- ▶ Material stop 300 mm
Order no. 570.510
- ▶ Connecting track, left
Order no. 570.511
- ▶ Connecting track, right
Order no. 570.512
- ▶ Roller conveyor, 2 m (150 kg/m)
Order no. 570.507
- ▶ Starter band saw blade package 1,620 x 13 x 0.65 mm each consisting of 1 pc. combi-toothing 6/10, 8/12, 10/14
Order no. 570.519

Technical data

PBS 120 Plus

Belt speed (m/min)	35/75
Band saw blade size (mm)	1,620 x 13 x 0.65
Motor 230V (kW)	0.25 / 0.37
Machine dimensions (mm)	810 x 530 x 450
Weight (kg)	38
Order no.	570.505

Sawing area

	0°	45°R	60°R
	120	90	55
	60 x 70	100 x 90	55 x 65
	120 x 120	90 x 90	55 x 55

Metal band saw blades ¹

Order no.	Dimensions in mm	Teeth per inch	VPE set = 5 pcs.
570.514	1,620 x 13 x 0.65	6/10	1
570.515	1,620 x 13 x 0.65	8/12	1
570.516	1,620 x 13 x 0.65	10/14	1

¹ Other bandsaw blades on request