

Double grinding machine

TS 175 SW

TS 175 SD P

TS 175 Pro



Fig.: TS 175 SW/TS 175 SD P

Standard equipment

- ▶ Smooth running, no-maintenance motor
- ▶ Protective hood closed at the sides
- ▶ Stable, adjustable workpiece supports
- ▶ High level of safety thanks to adjustable spark deflector
- ▶ Suitable for grinding, deburring and sharpening tools of all kinds, metal profiles etc.
- ▶ Circuit breaker and under-voltage release
- ▶ Spark/eye protection on both sides
- ▶ Connecting cable with two-pin earthed plug (for all SW models)
- ▶ Connecting cable with CEE plug 16 A (for all SD P models)
- ▶ 1x coarse and fine grinding wheel
- ▶ 12-month warranty for single-shift operation

Accessories

- ▶ Machine stand with dip tank,
Dimensions: 355 x 300 mm, Weight: 12 kg
Order no. 350.435
- ▶ Wall bracket
Order no. 315.035
- ▶ Separate replacement grinding wheel
coarse standard corundum
Order no. for TS 175: 317.526
- ▶ Separate replacement grinding wheel
fine standard corundum
Order no. for TS 175: 317.527
- ▶ Wheel dresser
Order no. 350.101
- ▶ Dust extraction system MA 400 D
(only TS 175 SD P and TS 175 Pro)
Order no. 330.295

Technical data

Machine dimensions without VP (mm)	230 x 440 x 210
Machine dimensions with VP (mm)	260 x 450 x 250
Suction piece Ø (mm)	42

TS 175 SW

Dimensions of the grinding wheel (mm)	175 x 25 x 32
Speed (1/min)	2,800
Motor AC 230 V (kW)	0.52, S3-25% (periodic)
Weight (kg)	15
Order no.	317.766

TS 175 SD P

Dimensions of the grinding wheel (mm)	175 x 25 x 32
Speed (1/min)	2,740
Three-phase current motor 400 V (kW)	0.7, S2-30 min (short time operation)
Weight (kg)	15
Order no.	317.761

TS 175 Pro

Dimensions of the grinding wheel (mm)	175 x 25 x 32
Speed (1/min)	2,750
Motor AC 230 V (kW)	0.7, S1 (continuous operation)
Weight (kg)	15
Order no.	317.840