

Double grinding machine

TS 200 SD P/Pro

TS 250 SD P/Pro

As combination units always with machine stand and brake (optionally with extraction system)



WHAT ELSE COULD YOU WISH FOR?
OUR DOUBLE GRINDING MACHINES

Fig.: TS 200 SD P/Pro with special equipment-foot switch

Standard equipment

- ▶ Smooth running, no-maintenance motor
- ▶ Emergency off push button
- ▶ Brake
- ▶ Machine stand/optionally with extraction system
- ▶ Protective hood closed at the sides
- ▶ Stable, adjustable workpiece supports
- ▶ High level of safety thanks to adjustable spark deflector
- ▶ Suitable for grinding, deburring and sharpening tools of all kinds, metal profiles etc.
- ▶ Circuit breaker and under-voltage release
- ▶ Spark/eye protection on both sides
- ▶ Connecting cable with CEE plug 16 A
- ▶ 1x coarse and fine grinding wheel
- ▶ 12-month warranty for single-shift operation

Special equipment

- ▶ Different colour shade (One-component RAL paint)
Order no. 309.010
- ▶ Foot switch emergency stop (can only be ordered in conjunction with brake, machine stand and/or extraction system)
Order no. 317.859

Accessories

- ▶ Separate spare grinding wheel coarse standard corundum
Order no. for TS 200: 317.532
Order no. for TS 250: 317.542
- ▶ Separate spare grinding wheel fine standard corundum
Order no. for TS 200: 317.533
Order no. for TS 250: 317.543
- ▶ Wheel dresser
Order no. 350.101

Technical data

Suction piece Ø (mm)	42
TS 200 SD P/Pro with brake and machine stand	
Dimensions of the grinding wheel (mm)	200 x 32 x 32
Machine dimensions without VP (mm)	270 x 470 x 1,050
Machine dimensions with VP (mm)	600 x 800 x 1,350
Speed (1/min)	2,550
Weight (kg)	60
TS 200 SD P with brake and machine stand	
Three-phase current motor 400 V(kW)	1.0, S2-30 min (short-time operation)
Order no.	317.774
TS 200 SD P with brake and machine stand with extraction system	
Three-phase current motor 400 V(kW)	1.0, S2-30 min (short-time operation)
Order no.	317.777
TS 200 Pro with brake and machine stand	
Three-phase current motor 400 V(kW)	0.75, S1 (continuous operation)
Order no.	317.846
TS 200 Pro with brake and machine stand with extraction system	
Three-phase current motor 400 V(kW)	0.75, S1 (continuous operation)
Order no.	317.847
TS 250 SD P/ Pro with brake and machine stand	
Dimensions of the grinding wheel (mm)	250 x 40 x 51
Machine dimensions without VP (mm)	520 x 530 x 1,110
Machine dimensions with VP (mm)	600 x 800 x 1,400
Speed (1/min)	1,400
Weight (kg)	85
TS 250 SD P with brake and machine stand	
Three-phase current motor 400 V(kW)	1.4, S2-30 min (short-time operation)
Order no.	317.775
TS 250 SD P with brake and machine stand with extraction system	
Three-phase current motor 400 V(kW)	1.4, S2-30 min (short-time operation)
Order no.	317.778
TS 250 SD Pro with brake and machine stand	
Three-phase current motor 400 V(kW)	0.8, S1 (continuous operation)
Order no.	317.851