

Double grinding machine TS 300 SD P

Optionally combined
with brake, machine
stand and extraction
system



Fig.: TS 300 SD P with machine stand

Standard equipment

- ▶ Smooth running, no-maintenance motor
- ▶ with emergency stop button and brake (only standard with art. no. 317.776 and 3177.779)
- ▶ Optional machine stand and extraction system
- ▶ Protective hood closed at the sides
- ▶ Stable, adjustable workpiece supports
- ▶ High safety comfort due to adjustable spark deflectors
- ▶ Suitable for grinding, deburring and sharpening of all kinds of tools, metal profiles, etc.
- ▶ Circuit breaker and under-voltage release
- ▶ Spark/eye protection on both sides
- ▶ Connecting cable with CEE plug 16 A
- ▶ 1x coarse and fine grinding wheel
- ▶ 12-month warranty for single-shift operation

Special equipment

- ▶ Different colour shade (One-component RAL paint)
Order no. 309.010
- ▶ Foot switch emergency stop (can only be ordered in conjunction with brake, machine stand and/or extraction system)
Order no. 317.859

Accessories

- ▶ Separate replacement grinding wheel coarse standard corundum
Order no. 317.622
- ▶ Separate replacement grinding wheel fine standard corundum
Order no. 317.624
- ▶ Wheel dresser
Order no. 350.101
- ▶ Machine stand with dip tank, Dimensions: 420 x 520 mm, Weight: 15 kg (only for 317.764)
Order no. 350.436
- ▶ Machine stand with extraction unit MA 600 D Motor 0.55 kW, extraction power 350 m³/h (only for 317.764)
Order no. 330.080

Technical data

Suction piece Ø (mm)	42
TS 300 SD P	
Dimensions of the grinding wheel (mm)	300 x 40 x 51
Machine dimensions without VP (mm)	350 x 530 x 340
Machine dimensions with VP (mm)	800 x 600 x 500
Speed (1/min)	1,250
Three-phase current motor 400 V (kW)	2.2, S2-30 min (short-time operation)
Weight (kg)	55
Order no.	317.764
TS 300 SD P with brake and machine stand	
Machine dimensions without VP (mm)	540 x 530 x 1,180
Machine dimensions with VP (mm)	800 x 600 x 1,400
Weight (kg)	85
Order no.	317.776
TS 300 SD P with brake, machine stand and extraction system	
Machine dimensions without VP (mm)	540 x 530 x 1,180
Machine dimensions with VP (mm)	800 x 600 x 1,400
Weight (kg)	90
Three-phase current motor 400 V (kW)	0.55
Suction capacity m ³ /h	350
Order no.	317.779